Climapac Packaged High Wall Air Conditioners

Heat Pumps & Air Conditioning Units



www.powrmatic.co.uk



Climapac Unit Duties

	1	1	
Capacity	Cooling Capacity	Btu/h	8,054
		kW	2.362
	Heating Capacity	Btu/h	7,706 (13,163 including electric heater)
		kW	2.23 (3.86 including electric heater)
Electrical	Power Supply	V~. Hz, Ph	230, 50, 1
	Power Input (kW)	Cooling	0.873
		Heating	0.879
	Starting Amp	Cooling	11
		Heating	9.8
	Running Amp	Cooling	4.4
		Heating	3.9
Performance (3 Fan Speeds)	EER	W/W	2.43
	COP	W/W	2.63
	Airflow Volume	m³/h	380
	Noise Level	dB(A)	<55
Dimensions	WxHxD	mm	1020 x 430 x 195
Weights	Net Weight	kg	42
	Gross Weight	kg	47
Inlet & Outlet Duct	Diameter	inches	8
		mm	200

- Note: A condensate drain is required to be fitted, from the rear drain point, to discharge condensed water accumulated during operation -

Key Features

Complete packaged unit with built in evaporator and condenser, no external unit required. Its wall mounted design enables air intake to condenser and discharge from condenser, through the wall via supplied inlet/outlet grilles.

The Climapac range of twin duct air conditioners from Powrmatic offers cooling, heating from heat pump, and extra PTC heating from the side mounted distinctive speaker style heaters.

The unit is fully remote controlled with temperature and timer options, and comes with a subtle LCD display, conveniently located on the lower front panel of the unit.

This highly attractive polished black finish twin duct unit will add equal value to the office, apartment or hotel room.

The Climapac does not require a F-Gas certified engineer to install.


Applications

- Offices
- Shops
- Apartments, Houses (Domestic use)
- Temporary Buildings
- Hotels, Motels & Serviced Suites

Powrmatic Ltd Hort Bridge Ilminster Somerset TA19 9PS

tel: +44 (0) 1460 53535 fax: +44 (0) 1460 52341 e-mail: info@powrmatic.co.uk web: www.powrmatic.co.uk






- Dental Surgeries
- Medical Practices
- Caravans



2 P P

safe









Powrmatic pursues a policy of continuous improvement in both design and performance of its products and therefore reserves the right to change, amend or vary specifications without notice. Whilst the details contained herein are believed to be correct they do not form the basis of any contract and interested parties should contact the Company to confirm whether any material alterations have been made since publication of this brochure.

For more information contact your local Powrmatic representative.





Powrmatic Ireland 45 Broomhill Close Tallaght Dublin 24

tel: +353 (0) 1452 1533 fax: +353 (0) 1452 1764 e-mail: info@powrmatic.ie web: www.powrmatic.ie